

ROTARY FIELD INDICATOR 8120

CAT IV / 1000 V



FEATURES

- High voltage phase indication for L1, L2, L3 with 3 LEDs
- Voltage Range: 100...1700 V; Frequency Range: 40...450 Hz
- Waterproof IP 65
- High voltage rotary field indication cw/ccw with 2 LEDs
- Developed for Utility Companies, Electric Power, Substation, Generators, Wind Power Stations
- Measurement category: CAT IV 1000V (highest security)
- Unique recognition of phase undervoltage or Faulty connection, using display with warning symbol
- High voltage protected Test Leads and Probes
- Soft plastic holster as shock absorber and improvement of grip

SCOPE OF SUPPLY

- | | |
|----------------------|---------------------------|
| 1 pc HDT Xtroid 8120 | 1 pc Protective carry bag |
| 3 pcs Test Leads | 1 pc Instruction Manual |
| 3 pcs Test Probes | 1 pc Carton Packaging |

TECHNICAL DATA

Model	8120
Display	6 LEDs (L1, L2, L3, R, L, W)
Voltage Range	100...1700V AC
Frequency Range	40...450 Hz
Input current	< 3,5 mA
Duration Time	S1, Continuous Operation
Measurement category	CAT IV 1000V
Protection degree	IP65
In compliance with	IEC/EN 61010-1, IEC/EN 61557-1 IEC/EN 61557-7
Certification	CE
Battery	not required
Dimension	approx. 220 x 110 x 45 mm
Weight	approx. 480 g